



WATER HEATERS WITH HEAT EXCHANGER FOR HORIZONTAL WALL MOUNTING							
CHARACTERISTICS							
Model	...	72268XSL	72265XSL	72270XSL	72266XSL	72280XBS	72281XBS
Rated volume	L	80	80	100	120	150	200
Energy efficiency class		C	C	C	C	C	C
Rated pressure	MPa	0,7	0,7	0,7	0,7	0,7	0,7
Rated voltage	V~	230	230	230	230	230	230
Rated electrical power	W	2 (3)	2 (3)	2 (3)	2 (3)	2 (3)	2 (3)
Heat exchanger surface area	m ²	0.36	0.35	0.35	0.59	0.59	0.77
Heat exchanger inside volume	L	1.31	1.71	1.71	2.85	2.85	3.73
Thermal power heat exchanger according EN 12897 (15-60°C; 15 l/min; 80°C)	kW	5.2	7	6.5	9	8.5	9.5
Warm-up time from 15-60 °C with heat exchanger (15 l/min; 80°C) (EN 12897)	min	25	23	30	27	40	50
Pressure drop across the coil	mbar	30	50	50	60	45	60
Standing loss	W	62	63	67	71	77	84
Weight	kg	32.5	29	34	42.5	55	69
CONNECTIONS							
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2M	G1/2M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2M	G1/2M
3: Temperature indicator		-	-	-	-	-	-
4: Control panel		-	-	-	-	-	-
5: Flange with a heating element		-	-	-	-	-	-
6: Heating coil - Feed		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
7: Heating coil - Return		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
DIMENSIONS							
A	mm	1115	825	1000	1165	1015	1255
B	mm	1030	740	915	1080	930	1170
C	mm	145	175	175	175	190	190
D	mm	385	460	460	460	586	586
E	mm	80	96	96	96	96	96
F	mm	400	474	474	474	595	595
G	mm	32	32	32	32	43	43
K	mm	135	150	150	150	190	190
L	mm	114	147	147	147	180	180
P	mm	255	300	300	300	360	360
R	mm	123	160	160	160	200	200
M	mm	770	415	587	753	560	780

Note:
The 150 - 200L water heaters must be installed on a wall only by using a special mounting brackets kit.