



ELECTRIC STORAGE WATER HEATERS WITH DRY TUBULAR HEATING ELEMENTS							
CHARACTERISTICS							
Model	...	WV03039D	WV05039D	WV08039D	WV08046D	WV10046D	WV12046D
Volume range	L	30	50	80	80	100	120
Load profile	...	S	M	M	M	M	M
Water heating energy efficiency class	...	C	C	C	C	C	C
Annual electricity consumption	kWh/annum	548	1401	1375	1366	1343	1333
Thermostat temperature presetting	°C	75	75	75	75	75	75
Mixed water at 40 °C	L	-	85	142	141	181	222
Rated pressure	MPa	0.7	0.7	0.7	0.7	0.7	0.7
Rated voltage	V~	230	230	230	230	230	230
Rated electrical power	kW	2x0,8	2x0,8	2x1,0	2x1,0	2x1,0	2x1,0
Net weight	kg	14	18	26	24	29	33
CONNECTIONS							
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		•	•	•	•	•	•
4: External thermostat		•	•	•	•	•	•
5: Flange with heating elements		•	•	•	•	•	•
6: Illuminated switch		•	•	•	•	•	•
DIMENSIONS							
A	mm	560	760	1125	835	1005	1170
C	mm	155	155	155	185	185	185
D	mm	387	387	387	462	462	462
E	mm	80	80	80	96	96	96
F	mm	410	410	410	484	484	484
G	mm	33	33	33	33	33	33

D - water heater with two dry tubular electric heating elements